



830

VIBAC® BOPP BOX SEALING TAPE 830

This Superior Performance packaging tape was designed for carton sealing, splicing, bundling, and other ultra demanding packaging applications. It offers super strength adhesive power in the heaviest applications.

| PROPERTIES | | | |
|--|-----------------------------------|--|--|
| Total thickness micron | 72 micron | Total thickness mils | 2.830 mils |
| Business | Industrial Professional | Industry | Bundling Carton Sealing Splicing |
| Backing Type | BOPP | Backing thickness micron | 50 micron |
| Adhesive type | Synthetic Rubber | Color | Clean |
| Tensile strength kg/cm | 8,03 kg/cm | Elongation at break | 200 % |
| Adhesion to steel g/cm | 611,8 g/cm | Rolling ball test (RBT) cm | <2 cm |
| Shear on cardboard | >200 hours | Backing thickness mils | 1.970 mils |
| Tensile strength lb./inch | 45.000 lb./inch | Adhesion to steel oz./inch | 56 oz./inch |
| Rolling ball test (RBT) inch | <0.78 inch | Service Temperature F° (Min / Max) | 30/140 °F |
| Service Temperature C° (Min / Max) | (-2)/60 °C | Application Temperature F° (Min / Max) | 50/110 °F |
| Application Temperature C° (Min / Max) | (10)/43 °C | Available width | 72.000 mm 48.000 mm 36.000 mm 144.000 mm 96.000 mm |
| Available length | 50.000 m 100.000 m 55.000 m | Packaging type | 6 rolls flat pack |